

HEATER DUCTS



PLIADUCT

100% rigid self-supporting gray PVC material with a ribbon-lock construction.
2" - 6" | 25ft 8" - 12" | 10ft
-23°C to +66°C



THERMAFLOW

Designed to transfer hot air up to 260°C (500°F) in tough winter conditions.
12" | 12ft, 25ft
-50°C to +260°C



AIR JET DUCTING

Used on propane heaters and rated up to 150°C (300°F).
12" | 12ft, 25ft
-40°C to +150°C



THERMASURGE

Used to supply or vent air on industrial, construction and commercial jobsites.
12" | 25ft
-15°C to +80°C

STEAM HOSE



STEAM MAXX CHLOROBUTYL

Chlorobutyl rubber gives superior resistance to heat aging and improved life expectancy.
3/4", 1", 1.5", 2" | 50ft
-40°C to +221°C



STEAM MAXX - EPDM

Extremely flexible hose for use with steam at temperatures up to 208°C
1/2", 3/4", 1", 1.25", 1.5", 2" | 50ft, 100ft
-40°C to +208°C



TEXTILE STEAM

For thawing, washdown at paper mills and food plants.
1/2", 3/4", 1" | 50ft, 100ft
-40°C to +170°C



CHALLENGER STEAM

Industrial steam cleaner machines and pressure washer machines.
500FT Reels (2 X 250FT)
Steam 165°C Water 121°C

MINING & DRILLING HOSE



EXTRA PRESSURE MAXX

Heavy duty 400 PSI air/water hose for use in demanding environments such as mining.
50ft | 100ft
-30°C to +100°C




STEEL MAXX

Mandrel built wire reinforced heavy duty air hose for high pressure pneumatic applications.
50ft | 100ft
-30°C to +80°C



CONAIR HOSE

Nitrile construction makes this product ideal where oil is a factor
3/4" | 25ft multiples, 100ft coils
1- 4" | 25ft multiples, 300ft coils
-30°C to +100°C



ANTI STATIC BLASTING HOSE

For loading of ammonium nitrate/fuel oil blasting agents used in mining and construction.
100ft, 200ft, 300ft
-35°C to 65°C



CMC MAXX

CMC (Corrugated Material Conducting) hose, utilizes split flanged couplings and is designed for abrasive suction and discharge service.
2" to 6" | 100ft 8" | 40ft
10" | 40ft 12" | 20ft
-40°C to +82°C



LW DRILLERS HOSE

A lightweight extremely portable 300PSI Red and 600PSI Yellow water hose.
1" | 100ft
-40°C to +60°C

HOSE ACCESSORIES



- Punch Locking Tools
- Cam & Groove Couplings
- Travis Couplings
- Powerlock Clamps
- Fat Lip Locking Arm Cams
- Type B Quick Couplings
- Double Bolt Clamps
- AND MORE

VAC & TANK TRUNK HOSE



PETRO MAXX

Suction and discharge hose for gas, distillate, kerosene, diesel, oil suspensions, emulsions and other petroleum products. 100 ft cut to multiples of 5ft -35°C to +93°C



MULTI MAXX

Designed to be used in multiple applications from water suction and discharge to petroleum transfer. 100 ft cut to multiples of 5ft -40°C to +121°C



POLAR MAXX

Petroleum suction and discharge hose designed to remain flexible in low temperatures. 100 ft cut to multiples of 5ft -50°C to +93°C



TIGER TAIL

Maximum abrasion protection for sewer jetting hose, expensive camera and utility inspection equipment. 25ft, 50ft -40°C to +60°C



WEAR MAXX

Extremely abrasion resistant hose for conveying wood, metal, rock, concrete, dust, etc. under vacuum. Corrugated for excellent flexibility. 6", 8" | 100ft 10" | 40ft -40°C to +82°C



FLOW MAXX

Heavy duty rubber hose that is excellent for construction, quarries, and general use. 3/4"-6" | 100ft cut to 5ft multiples 8"-12" | 40ft cut to 5ft multiples -32°C to +82°C




UF2

For dry applications where severe abrasion is a factor. 6"-8" -40°C - +60°C



180AR

Suction and discharge of dry materials such as sand, crushed rock, cement etc. 1 1/4 - 6" | 100ft 8" | 50ft cut to multiples of 5ft 10" | 20ft cut to multiples of 5ft -40°C - +60°C



EPDM WATER SUCTION

For agricultural chemicals and general industrial use. External helix provides for easy drag. 100ft cut to multiples of 5ft -40°C - +60°C



SCORPION WATER

Hybrid garden hose with a polymer construction that remains flexible in cold temperatures. 50ft, 100ft -40°C to +65°C



CHALLENGER CES

For agricultural chemicals, general industrial use and oilfield service. 1.5-6" | 100ft cut to 5ft multiples -40°C - +60°C



PRESSURE WASHER

For use with pressure washer machines 4000PSI - Black, Blue, Yellow 6000PSI - Grey -30°C to +121°C

FLUSH HOSE



SPOR-MMI6X600

Sewer flushing hose with synthetic fiber braid reinforcement. 6" - 10"



HPBU-MI6X600

Sewer flushing hose with synthetic fiber braid reinforcement. 3/4"-1"



LLGR-MM08

4000 PSI lateral line hose with synthetic fiber braid reinforcement. 1/2"-3"



LLBU-MM08


3000 PSI lateral line hose with synthetic fiber braid reinforcement. 1/2" - 6"

FIRE HOSE



FOREST LITE I&2

A single jacket, polyurethane lined lightweight hose intended for use in wildland fire suppression. 1"-1 1/2" | 50ft, 100ft



INDUSTRIAL MILL - IMD

Economical pump discharge and washdown hose. 25ft | 50ft | 75ft | 100ft -20°C to +65°C



ARMOURED REEL

Recommended for skid units, booster reels, industrial reels, forestry and wildland applications. 1" | 50ft, 100ft, 150ft, 200ft

LAYFLAT



CONTRAFLEX

Designed for discharging water and oil contaminated water at high pressures. 25ft multiples & 300ft coils -30°C to +95°C



PVC LAYFLAT

Designed for use where higher working pressures are required. Multiples of 25ft to 300ft Maximum -10°C to +60°C

WWW.CROSSCOUNTRYCANADA.CA

780-962-6559

