



## Morooka VDR Series

Featuring a 360° revolving upper structure that allows that operator to deposit spoil exactly where needed.

**MOROOKA**



# SPECIFICATIONS

MST-200VDR			MST-1500VDR			MST-2200VDR		
LENGTH	9' 4"		LENGTH	18' 6"		LENGTH	19' 8"	
WIDTH	4' 11"		WIDTH	8' 6"		WIDTH	9' 8"	
HEIGHT	7' 10"		HEIGHT	10'		HEIGHT	10' 6"	
MIN GROUND CLEARANCE	11"		MIN GROUND CLEARANCE	20"		MIN GROUND CLEARANCE	21"	
TRACK WIDTH	12"		TRACK WIDTH	28"		TRACK WIDTH	31 ½"	
LENGTH OF BED	4' 10"		LENGTH OF BED	9'		LENGTH OF BED	10' 9"	
WIDTH OF BED	4' 6"		WIDTH OF BED	7' 8"		WIDTH OF BED	9' 6"	
WEIGHT	4,500 lbs.		WEIGHT	28,100 lbs.		WEIGHT	35,273 lbs.	
FUEL CAPACITY	13.2 gal.		FUEL CAPACITY	53 gal.		FUEL CAPACITY	65 gal.	
ENGINE MFG.	KUBOTA® V1505		ENGINE MFG.	CAT® C7.1		ENGINE MFG.	CAT® C7.1	
HORSEPOWER	24		HORSEPOWER	225		HORSEPOWER	250	
TRANSMISSION	HST		TRANSMISSION	HST		TRANSMISSION	HST	
MAXIMUM LOAD	4,400 lbs.		MAXIMUM LOAD	15,435 lbs.		MAXIMUM LOAD	24,255 lbs.	
TRAVEL SPEED	0 - 3.5 MPH		TRAVEL SPEED	0 - 7.5 MPH		TRAVEL SPEED	0 - 8 MPH	
GROUND PRESSURE (EMPTY/LOADED)	2.7 PSI	5.5 PSI	GROUND PRESSURE (EMPTY/LOADED)	4 PSI	6.2 PSI	GROUND PRESSURE (EMPTY/LOADED)	3.5 PSI	6.6 PSI